# C96900HT



Alloy C96900HT, also designated CuNi15Sn8A, is spinodal hardened (CX), reflecting properties similar to copper beryllium alloys.

Product description	Copper-nickel		
Solids	Consult mill		
Tubes	2" to 14" O.D.*		
Rectangles	Consult mill		
Standard lengths	24"**		
Shape / form	semi-finished, mill stock or near-net shapes, an- ode, bar stock, billet / bloom, squares, hex, plate, profile or structural shape, flats / rectangular bar		

<sup>\*</sup>Consult mill for wall thickness

# Typical uses:

Industrial / off-road / mining / heavy equipment

- Bushings, bearings, fittings, wear plates

#### Oil / gas

 Bushings, bearings, fittings, components for oil

#### Aircraft / aerospace

- Landing gear bushings and bearings



<sup>\*\*</sup>Consult mill for other lengths

### C96900HT

Chemical composition			
Cu (%)	Sn (%)	Ni (%)¹	Mn (%)
76.80	8.00	15.00	0.20

Chemical composition according to ASTM B505/B505M-23

## Mechanical properties

Tensile strength, min				Elongation, in 4D or 2 in. or 50 mm min		Remarks
ksi	MPa	ksi	MPa	%	min BHN	
110	758	105	724	4		Heat treated Rockwell C32

Mechanical properties according to ASTM B505/B505M-23

# Key features and benefits:



## Wieland Concast certifications

- AS9100:2016-certified quality management system
- ISO 9001:2015-certified quality management system

Wieland Concast | 14315 State Route 113 | Wakeman, OH 44889

P 440-965-4455 | sales@concast.com | concast.com

