

Continuous-Cast Product List

Common Continuous-Cast Products (nonproprietary) • Product Forms – Size Ranges

Copper Alloy UNS No.	Product Description	Solid Bar Stock		Tubes		Rectangles		Near- Net Shape	Solid Hex Bar	Hex Tube
		Avail.	Size Range	Avail.	Size Range	Avail.	Size Range			
C83600	Leaded Red Brass	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C83800	Leaded Red Brass	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C84200	Leaded Semi-Red Brass	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C84400	Leaded Semi-Red Brass	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C84800	Leaded Semi-Red Brass	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C85700	Leaded Yellow Brass	X	1/2" to 13" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C86200	Manganese Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C86300*	Manganese Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C86400	Manganese Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C86500	Manganese Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C86700	Manganese Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C87850	Silicon Brass	X	Consult Mill	X	Consult Mill	X	Consult Mill	X	X	X
C89320	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89325	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89520	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89831	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89833	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89835*	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C89844	Bismuth Tin Bronze	X	1/2" to 10" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C90300*	Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C90500	Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C90700	Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C90800	Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C90810	High Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C91000	Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C91100	High Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C91300	Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C91600	High Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C91700	High Tin Bronze	X	1" to 6" O.D.	X	1" to 6" O.D.	X	Up to 10"	X	X	X
C92200	Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C92300	Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C92500	Nickel-Phosphor Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C92700	Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C92800	Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C92900	Leaded Nickel-Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93200*	Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93400	High-Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X

*Standard-stocked alloy.

Note: Please consult mill for minimum I.D., minimum thickness and minimum wall thickness.



Continuous-Cast Product List (continued)

Copper Alloy UNS No.	Product Description	Solid Bar Stock		Tubes		Rectangles		Near- Net Shape	Solid Hex Bar	Hex Tube
		Avail.	Size Range	Avail.	Size Range	Avail.	Size Range			
C93500	High-Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93600	High-Leaded Tin Bronze	X	1/2" to 13" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93700	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93800	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C93900	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C94000	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 10"	X	X	X
C94100	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 10"	X	X	X
C94300	High-Leaded Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 10"	X	X	X
C94700	Nickel-Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C94700HT	Nickel-Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C94800	Leaded Nickel-Tin Bronze	X	1/2" to 10" O.D.	X	1" to 16" O.D.	X	Up to 20"	X	X	X
C95200	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95300	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95300HT	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95400*	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95400HT	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95410	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95410HT	Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95500*	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95500HT	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95510*	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 13" O.D.	X	Up to 15"	X	X	X
C95520HT	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95600	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95800	Nickel-Aluminum Bronze	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C95900*	Aluminum Bronze	X	1" to 5" O.D.		Consult Mill	X	Up to 7"	X	X	X
CONCAST380*	Aluminum Bronze	X	1" to 5" O.D.			X	Up to 10"	X	X	
C96400	Copper-Nickel	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C96900HT	Copper-Nickel	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 15"	X	X	X
C97300	Nickel Silver Bronze	X	3/4" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 14"	X	X	X
C97600	Nickel Silver Bronze	X	3/4" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 14"	X	X	X
C97800	Nickel Silver Bronze	X	3/4" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 14"	X	X	X
C99500	Special Alloy	X	1/2" to 9" O.D.	X	1-1/8" to 9" O.D.	X	Up to 14"	X	X	X

*Standard-stocked alloy.

Note: Please consult mill for minimum I.D., minimum thickness and minimum wall thickness.

