

# Wrought Product List

Copper Alloy UNS No.	ASTM Spec	Temper						Product Description	Round Size Range	Hex/Oct Size Range
C24000	B927		H01	H02	H04			Low Brass, 80%	0.375 to 2.5	0.375 to 2.0
C26000	B927		H01	H02	H04			Cartridge Brass, 70%	0.375 to 2.5	0.375 to 2.0
<b>C31400*</b>	<b>B140</b>			<b>H02</b>	<b>H04</b>			<b>Leaded Commercial Bronze</b>	<b>0.375 to 2.0</b>	<b>0.375 to 2.0</b>
C31600	B140			H02	H04			Leaded Commercial Bronze (nickel-bearing)	0.375 to 2.0	0.375 to 2.0
<b>C51000*</b>	<b>B139</b>				<b>H04</b>		<b>H08</b>	<b>Phosphor Bronze 5% A</b>	<b>0.375 to 2.5</b>	<b>0.375 to 2.0</b>
C52100	B139				H04			Phosphor Bronze 8% C	0.375 to 2.5	0.375 to 2.0
C53400	B139				H04			Phosphor Bronze B-1	0.375 to 2.5	0.375 to 2.0
<b>C54400*</b>	<b>B139</b>				<b>H04</b>			<b>Phosphor Bronze B-2</b>	<b>0.375 to 2.5</b>	<b>0.375 to 2.0</b>
<b>C63000*</b>	<b>B150</b>	<b>HR50</b>						<b>Nickel Aluminum Bronze</b>	<b>0.375 to 10.0</b>	<b>0.5 to 2.0</b>
<b>C63020*</b>	<b>B150</b>	<b>TQ50</b>						<b>Nickel Aluminum Bronze</b>	<b>0.75 to 4.0</b>	
<b>C64200*</b>	<b>B150</b>	<b>HR50</b>						<b>Aluminum Bronze</b>	<b>0.1875 to 6.0</b>	<b>0.5 to 2.0</b>
C64210	B150	HR50						Aluminum Silicon Bronze	0.3125 to 3.0	0.5 to 2.0
C65100	B98			H02	H04	H06		Low-Silicon Bronze B	0.375 to 2.0	0.375 to 2.0
<b>C67300*</b>				<b>H02</b>				<b>Manganese Bronze</b>	<b>0.75 to 3.0</b>	
C67600	B138			H02	H04			Manganese Bronze	0.75 to 2.0	
C69400	B371				H04			Silicon Red Brass	0.375 to 2.0	0.375 to 2.0
C69430	B371				H04			Silicon Red Brass	0.375 to 2.0	0.375 to 2.0

\*Standard-stocked alloy.